$\begin{bmatrix} 11 \end{bmatrix}$ 3X \oslash 0.44 \lnot HOLE FOR SPIKING [281] 11.0 [1356] ∅ 53.4 MAXIMUM FOOTPRINT [726] **Ø 28.6** [267] Ø10.5 MAXIMUM FOOTPRINT WITH LEGS RETRACTED TRANSPORT FOOTPRINT [385] 15.1 COLUMN **FULL TRAVEL** [956] 37.6 MAXIMUM HEIGHT WITH LEGS RETRACTED [567]
22.3
MINIMUM HEIGHT
WITH LEGS
RETRACTED [1488] 58.6 [645] 25.4 TRANSPORT **MAXIMUM** HEIGHT 19223 INITIAL RELEASE 1/17/2020 VH REV ECN# ZONE DESCRIPTION DATE BY APPROVED **REVISION HISTORY** QUICKSET® **NOTES:** .XX ± 0.01 OF QUICKSET DEFENSE TECNOLOGY LLC. AND MAY BE USED BY DTHERS ONLY AS AUTORIZED BY QUICKSET. ALL RIGHTS RESERVED .XXX ± 0.005

ANGULAR ± 0.5°

INSIDE CORNERS 0.030 MAX RAD

PER ASME Y14.36 & B46.1

requiring a license, without prior written approval from the U.S. ALL DIMENSIONS ARE IN INCHES DEPARTMENT OF COMMISSIONS ARE I

UNDER THE COPYRING LAWS.

This document contains technology subject to the U.S. Export

Administration Regulations (EAR) and may not be exported o

ansferred by any means to any person, country, or company

requiring a license or other authorization, or for end uses

TRIPOD, SAM HP LASER 3 SEC LEG

4-73502-ICD

SEE BOM

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY.

2. [DIMENSION] ARE IN MILLIMETERS.